

316L Stainless Steel
Wet/Wet Differential
Constant Current/Constant Voltage
Fittings/Cable
Uncompensated/Non-Silicone Oil

DP86 Series

The DP86 Series differential pressure sensor is a double-sided, media compatible, piezoresistive silicon pressure sensor packaged in a 316L stainless steel housing. The series can be configured for o-ring mounting or threaded process fittings. The sensing package utilizes silicone oil to transfer pressure from the two 316L stainless steel diaphragms to a single sensing element.

This series is designed for high performance, low pressure applications where differential pressure measurement is required. The stainless steel package makes it suitable for use in liquids and corrosive environments.



FEATURES

- O-Ring Mount/Threaded Process Fittings
- Up to -40°C to +125°C Operating Range
- Up to ±0.1% Pressure Non Linearity
- Solid State Reliability
- Low Pressure

APPLICATIONS

- Level Controls
- Tank Level Measurement
- OEM Equipment
- Corrosive Fluids and Gas Measurement Systems
- Flow Measurements

Product Definition

Model	Pressure Ranges	Type (G = Gage A = Absolute D = Differential)	Span (typ)	Supply		Operating Temperature	Unique Feature
				Voltage	Current		
DP86	0 – 1, 5, 15, 30, 50, 100, 300, 500psi	D	See Sensitivity		1.5mA	-40°C to +125°C	O-ring mount
DP86CC- CBL	0 – 1, 5, 15, 30, 50, 100, 300, 500psi and 0 – 35Bar	D	100mV		1.5mA	-40°C to +125°C	O-ring mount
DP86CC- FTG	0 – 1, 5, 15, 30, 50, 100, 300, 500psi and 0 – 35Bar	D	100mV		1.5mA	-40°C to +125°C	Threaded process fittings
DP86CV- CBL	0 – 1, 5, 15, 30, 50, 100, 300, 500psi and 0 – 35Bar	D	80, 100mV	10Vdc		-40°C to +125°C	O-ring mount
DP86CV- FTG	0 – 1, 5, 15, 30, 50, 100, 300, 500psi and 0 – 35Bar	D	80, 100mV	10Vdc		-40°C to +125°C	Threaded process fittings
DP86NS	0 - 15, 30, 50, 100, 300, 500psi	D	See Sensitivity		1.5mA	-55°C to +100°C	O-ring mount
DP86U- FTG	0 – 1, 5, 15, 30, 50, 100, 300, 500psi	D	See Sensitivity		1.5mA	-40°C to +125°C	Threaded process fittings

NORTH AMERICA

Measurement Specialties
45738 Northport Loop West
Fremont, CA 94538
Tel: 1-800-767-1888
Fax: 1-510-498-1578
Sales: pfg.cs.amer@meas-spec.com

EUROPE

Measurement Specialties
(Europe), Ltd.
26 Rue des Dames
78340 Les Clayes-sous-Bois, France
Tel: +33 (0) 130 79 33 00
Fax: +33 (0) 134 81 03 59
Sales: pfg.cs.emea@meas-spec.com

ASIA

Measurement Specialties
(China), Ltd.
No. 26 Langshan Road
Shenzhen High-Tech Park (North)
Nanshan District, Shenzhen 518057
China
Tel: +86 755 3330 5088
Fax: +86 755 3330 5099
Sales: pfg.cs.asia@meas-spec.com

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.