

P1200



- Rugged Design for Harsh Environments
- High Burst Pressure Limit
- High Reliability
- Low and High Level Output Signals



DESCRIPTION

The P1200 Series pressure transducers and transmitters provide high accuracy pressure measurement of liquids and gases. These robust transducers combine hybrid electronics with highly reliable strain gauge sensing technology to offer superior performance in rugged applications. Constructed from media compatible 17-4 PH stainless steel, the P1200 provides exceptional performance in extreme environments.

Accuracy of the P1200 is guaranteed to be within $\pm 0.20\%$ F.R.O. over a wide temperature compensated range of -20°C to 80°C . The P1200 is available with either cable or connector terminations or offers a variety of outputs including 0-20 mV, 0-100 mV, 0-5 V and 4-20 mA. Six selectable pressure ports are available to suit most application requirements. Pressure ranges include 0-75 psi to 10,000 psi (0-5 bar to 700 bar) and can be referenced in absolute, sealed or vented gauge. The P1200 Series maintains a high burst rate of greater than 20x the rated pressure and 5x overpressure limit without damage to the sensor due to a positive over travel stop.

FEATURES

- Typical Accuracy of $< \pm 0.15\%$ F.R.O.
- Cable/Connector Termination
- Stainless Steel Media Isolated
- 5x Overpressure Protection
- High and Low Level Output

APPLICATIONS

- Vehicle Brake System Monitoring
- Gas Production
- Farm Machinery
- Hydraulic Control Monitoring

P1200

PERFORMANCE SPECS

| Series | P1200 | P1230 | P1240 | P1260 | P1280 |
|-------------------------|---------------------|---------------------|---------------------|-----------|---|
| Model Number | P1221/3 | P1231/3 | P1241/3 | P1261/3 | P1281/3 |
| Input Voltage | 10VDC (12 V max) | 10VDC (12 V max) | 10VDC (12 V max) | 18-32VDC | 10-36VDC |
| Impedance (ohms) | 1000 to 1600 | - | - | - | - |
| Current (mA max) | 10 | 12 | 12 | 25 | - |
| Full Range Output (±2%) | 20mV | 100mV | 5VDC | 5VDC | 4-20 mA (16 mA±2%) |
| Impedance (ohm) | 1000 ±50 | <10 | <10 | <10 | Load Resistance 1300 ohm (max) at 36VDC |
| Current (mA max) | - | - | 5 | 5 | - |
| Frequency Response | 2.5 to 40 kHz | 2 kHz | 2 kHz | 1 kHz | 1 kHz |
| Residual Unbalance | <±2 | <±2 | <±2 | <±2 | 4.0 mA +2-0 |
| Weight oz (gm) | 3.4 (95) | 4.4 (125) | 4.4 (125) | 4.4 (125) | 4.4 (125) |

COMMON SPECIFICATIONS

Pressure Ranges

High (psi) 0-75, 100, 150, 220, 250, 350, 500, 750, 1000, 1500, 2200, 2900, 3500, 5000, 7500, 10,000

(bar) 0-5, 7, 10, 15, 20, 25, 35, 50, 70, 100, 150, 200, 250, 350, 500, 700

DIN (bar) 6, 10, 16, 25, 40, 60, 100, 160, 250, 400, 600

Pressure References Vented gauge (Sensors should only breathe dry noncorrosive gases. Sealed gauge and absolute to special order).

Pressure Limit >5x full range pressure or 12,000 psi (830 bar), whichever is less.

Burst Pressure >20 x full range pressure or 22,000 psi (1,520 bar), whichever is less

Pressure Media Liquids or gases compatible with 17-4 PH stainless steel

Combined Non-linearity, Hysteresis

and Non-repeatability <±0.15% F.R.O. (typ); ±0.20% F.R.O. max (BSL) – high range

Temperature Range

Operable -65°F to 185°F (-54°C to 85°C) [P1221/4 -65°F to 250°F (-54°C to 120°C)]

Compensated -4°F to 185°F (-20°C to 85°C) [P1221/4 -4°F to 212°F (-20°C to 100°C)]

Storage -65°F to 250°F (-54°C to 120°C)

Combined Thermal Zero

And Sensitivity Shift <±0.010% F.R.O./°F (±0.02% F.R.O./°C) over compensated temperature range

Total Thermal Error Band*

(including NLH) %F.R.O.

-4° to 185°F (-20° to 85 °C ±1.2% typical, ±2.0% max. (over compensated temperature range)

Shock Resistance 1000 g for 5 msec

Vibration Resistance Surpasses MIL STD810C Method 514-2 Curve L and EUROCAE ED 14A/RTCA 160A

Humidity

Connector Version 95% Relative humidity

Cable Version Immersible to IP67

EMC

Emissions to EN55022 (CISPR 22) Limit B; Radiated Immunity to IEC 801-3 Level 3 10 V/m;


Burst Transients to IEC 801-4 Level 3 (2kV); Electrostatic Discharge to IEC 801-2 Level 2 (4kV

contact); Surges to IEC 801-5 class 3 (2kV).

Insulation Resistance 500 MOhm at 50 VDC

P1200


DIMENSIONS



| Adapters | | | | | |
|--------------------|-------------|-------------|-------------|---------------|-------------|
| Thread Size | Code Welded | A | B | Code Screw In | B |
| G1/4A (BSP) (F) | 0001 | | | | |
| G1/4A (BSP) (M) | 0002 | 0.46 (11.7) | 0.67 (16.9) | 0022 | 0.76 (17.6) |
| M14 x 1.5 (M) | 0003 | 0.40 (10.2) | 0.61 (15.4) | 0023 | 0.61 (15.6) |
| 7/16"-20UNF-2A (M) | 0004 | 0.56 (14.3) | 0.77 (19.5) | 0024 | 0.77 (19.6) |
| 1/4"-18NPT (M) | 0005 | 0.55 (14.0) | 0.76 (19.2) | 0025 | 0.81 (20.6) |
| M10 x 1.0 (F) | 0006 | | 0.60 (15.2) | 0026 | 0.60 (15.2) |
| 1/4"-18NPT (F) | 0009 | | | | |

P1200

ORDERING INFORMATION



Example: P1283-0023-10KPSS = 4 to 20mA output, connector outlet, screwed in M14 male port, 10,000 psi sealed gauge

NORTH AMERICA

Measurement Specialties
45738 Northport Loop West
Fremont, CA 94538
Tel: 1-800-767-1888
Fax: 1-510-498-1578
Sales: pfg.cs.amer@meas-spec.com

EUROPE

Measurement Specialties
(Europe), Ltd.
26 Rue des Dames
78340 Les Clayes-sous-Bois, France
Tel: +33 (0) 130 79 33 00
Fax: +33 (0) 134 81 03 59
Sales: pfg.cs.emea@meas-spec.com

ASIA

Measurement Specialties
(China), Ltd.
No. 26 Langshan Road
Shenzhen High-Tech Park (North)
Nanshan District, Shenzhen 518057
China
Tel: +86 755 3330 5088
Fax: +86 755 3330 5099
Sales: pfg.cs.asia@meas-spec.com

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.