



# Model 4203 Accelerometer



## performance specifications

All values are typical at  $\pm 24^{\circ}\text{C}$ , and 10 Vdc excitation unless otherwise stated. Measurement Specialties reserves the right to update and change these specifications without notice.

Parameters	-06	-08	-10	-20	-30	Notes
<b>DYNAMIC</b>						Dash Number
Range(g)	$\pm 6$	$\pm 7.5$	$\pm 10$	$\pm 20$	$\pm 30$	
Sensitivity (mV/g)	333	267	200	100	67	$\pm 5\%$
Standard Frequency Response (Hz)	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60	Or custom order
Customizable LP Corner Range (Hz)	5 to 100	5 to 100	5 to 100	5 to 100	5 to 100	-3dB, -160dB/decade
Shock Limit (g)	5000	5000	5000	5000	5000	
Non-Linearity (% FSO)	$\pm 1$	$\pm 1$	$\pm 1$	$\pm 1$	$\pm 1$	
Transverse Sensitivity (%)	$<3/<1.5$	$<3/<1.5$	$<3/<1.5$	$<3/<1.5$	$<3/<1.5$	Standard/Optional
Zero Acceleration Output (mV)	$\pm 100$	$\pm 100$	$\pm 100$	$\pm 100$	$\pm 100$	From 2.5Vdc bias
Thermal Zero Shift (%FSO/50°C)	$\pm 2.5/\pm 1.5$	$\pm 2.5/\pm 1.5$	$\pm 2.5/\pm 1.5$	$\pm 2.5/\pm 1.5$	$\pm 2.5/\pm 1.5$	Standard/Optional
Thermal Sensitivity Shift (%/50°C)	$\pm 2.5/\pm 1.5$	$\pm 2.5/\pm 1.5$	$\pm 2.5/\pm 1.5$	$\pm 2.5/\pm 1.5$	$\pm 2.5/\pm 1.5$	Standard/Optional
<b>ELECTRICAL</b>						
Excitation (Vdc)	8 to 16	8 to 16	8 to 16	8 to 16	8 to 16	
Current (mA)	$<5$	$<5$	$<5$	$<5$	$<5$	
Output Impedance ( $\Omega$ )	$<100$	$<100$	$<100$	$<100$	$<100$	
Insulation Resistance (M $\Omega$ )	$>100$	$>100$	$>100$	$>100$	$>100$	@50Vdc
<b>PHYSICAL</b>						
Case Material	Al Alloy	Al Alloy	Al Alloy	Al Alloy	Al Alloy	Anodized
Cable (Teflon Jacket, 5 wire+shield)	24 AWG	24 AWG	24 AWG	24 AWG	24 AWG	Teflon insulated
Weight (grams)	$<60$	$<60$	$<60$	$<60$	$<60$	Without cable
Mounting			M3 Screws			4X
<b>ENVIRONMENTAL</b>						
Operating Temperature ( $^{\circ}\text{C}$ )			-40 to +125			
Sealing						Potted Construction

### PART NUMBERING

4203-XX-YY-ZZ-WW where XX, YY, ZZ represent the g ranges for each of the 3 axes, WW is optional frequency cutoff.

**Wiring color code:** +Input = Red; -Input/+Output = Black; +Output X = Green; +Output Y = Blue; +Output Z = White

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.

## ordering info

### North America

Measurement Specialties, Inc.  
1000 Lucas Way  
Hampton, VA 23666  
Tel: 1-800-555-1551  
Fax: 1-757-766-4297  
Sales: sales@meas-spec.com

### Europe

Measurement Specialties, Inc.- Humirel  
105 av. Du General Eisenhower BP  
23705  
31037 Toulouse, Cedex 1, France  
Tel: +33 (0) 561 194 543

### Asia

Measurement Specialties, Inc  
No. 26 Langshan Road  
Shenzhen High-Tech Park (North)  
Nanshan District, Shenzhen 518107  
Tel: +86 755 33305088  
Fax: +86 755 33305099  
Sales: sales.china@meas-spec.com